

## COMPACT CARS

1. Compact cars will consist of rear wheel drive cars (106 wheelbase or smaller) front wheel drive cars of any wheelbase (except for 1985 and older Eldorado, Toronado, and Riviera).
2. All gas tanks must be moved inside of the car must have a 5 gallon metal gas can inside of car secured and covered. Cars with gas tanks on the outside and/or plastic cans will not be permitted to run. Gas tank protectors cannot go past half way point of rear door, or half way of rear compartment, and may not touch the rear deck. Fuel injected cars: Any hose connection must be done in braided steel line or fuel injection hose clearly marked, must have a kill switch on the fuel pump, and all fitting must be double clamped. These rules are for driver's safety as fuel injection systems are pressurized and can burst regular rubber fuel line. . A kill switch on cars with electronic fuel pumps is mandatory.
3. Leaf springs: no leaf spring conversions will be permitted. Maximum 5 leafs per side with minimum 2" stair step in cars with factory leafs. Struts may be spaced, but must still move and adhere to 20" height limit.
4. Bumpers: original factory bumpers shocks must be used; you may put any 70's and newer car OEM bumper on compacts. Bumper shocks from compact cars will only be allowed 1 3/4" maximum on tube diameter. No 80's style bumper shocks. Compact cars must have safety bar behind the driver's seat from post to post, 3" maximum diameter.
5. Cars may be welded using 3" welds every 3" or 6" welds every 6" on passenger doors, trunks, and station wagon tailgates (in lieu of outside welds, station wagon tailgates may have a 3"x3"x1/4" angle 3" long welded on inside every 3" on the bottom only) NOT BOTH. You may not weld both inside and outside. Cars may be wired, banded, bolted and chained in the same way. Driver's door may be welded solid if desired. Banding every 6" on passenger doors and trunks; bands may be no larger than 1-1/4" wide. Chains must be at least 1/4". No welding or bolting to frame and bumpers. BODY SEAMS MAY NOT BE WELDED. Wires from body to roof (includes windows) are NOT PERMITTED.
6. Patches: rusted cars may be patched with tin only (STRICKLY INFORCED.) Stitch weld patches 1" on 1" off. Patch one side only (YOU MUST PROVE THE RUST.)
7. Radiators cannot be relocated. They may be banded (2 bands maximum) to core support vertically or horizontally.
8. Just because it's not in the rules doesn't mean you can do it! If you are not sure, call or e-mail to ask. Don't just show up and expect to run.